BELZONA REPAIRS AND PROTECTS WATER TREATMENT PLANT

CUSTOMER

Nuclear Power Plant, Lancashire - UK

APPLICATION DATE

March 2007

APPLICATION SITUATION

Sulphuric acid containment bund around tank and pipeworkAcid dilution bund.Sulphuric acid transfer channel. All located in the demineralisation (water-treatment)plant of the power station.

PROBLEM

The concrete bunds and channel were badly deterioted from the acid. Previously applied competitor coating had failed to protect the concrete substrate.

PRODUCTS

Belzona® 4131 (Magma Screed) Belzona® 4181 (Magma AR Screed) Belzona® 4311 (Magma CR-1)

SUBSTRATE

Concrete and a failed competitor coating

APPLICATION METHOD

The application was carried out in accordance with Belzona Know-How system leaflets TCC-9 and TCC-15.

BELZONA FACTS


The customer was impressed that this permanent repair was completed in five days. The first application was recently inspected after eight months because of an acid spillage during maintenance and the Belzona was still as good as the day it was first applied. Belzona® 4311 was chosen because the bund is frequently exposed to spillage and has proven to withstand the chemicals. Belzona® 4181 allowed rebuilding and protection of the channels whilst providing erosion resistance to the flow of acid.

PICTURES

- 1. Substrate rebuilt using Belzona® 4131
- 2. Protection provided by Belzona® 4311 coating
- 3. Channels rebuilt and lined with Belzona® 4181
- 4. Completed application back in service









For more examples of Belzona Know-How In Action, please visit http://khia.belzona.com



UK • USA • Canada • China www.belzona.com

