BELZONA SOLVES THROUGH WALL CORROSION ON SLUDGE BUFFER TANK

CUSTOMER

Sewage treatment site, UK

APPLICATION DATE

September 2013

APPLICATION SITUATION

Sludge buffer tank fabricated from glass coated mild steel.

PROBLEM

The sludge buffer tank was suffering from through wall corrosion at the vapour interface level. The tank could not be taken off line for an extended time which traditional repair methods would require due to demand. Any repairs would have to be carried out without hot works or the use mechanical equipment due to the risk of sparks.

PRODUCTS

Belzona 1161 (Super UW-Metal) Belzona 5831 (ST-Barrier)

SUBSTRATE

Glass coated mild steel

APPLICATION METHOD

The application was carried out in accordance with Belzona Know-How System Leaflet TCC-3. After cleaning the areas, surface preparation by hand abrasion was carried out. Repair plates pre-coated with Belzona 5831 were cold plate bonded over the through wall defects using Belzona 1161. Finally Belzona 5831 was applied to the entire repair areas.

BELZONA FACTS

The client had only been able to run the Buffer tank at a reduced capacity of 65%. No other alternatives were deemed to provide a viable solution to the customers requirements. Belzona solution kept the site running with minimal disruption and was carried out without hot works or the use mechanical equipment so presenting no risk of sparks.

PICTURES

- 1. Close up view of through wall defects
- 2. Plate bonding with Belzona 1161
- 3. Repairs coated with Belzona 5831
- 4. Completed application









For more examples of Belzona Know-How In Action, please visit http://khia.belzona.com



UK • USA • Canada • China www.belzona.com

