

BELZONA REPAIRS CRUSHER'S BASE

CUSTOMER

Mine, BA, Brazil

APPLICATION DATE

January 2006

APPLICATION SITUATION

Interior of the crusher's base.

PROBLEM

Over time, the vibration of the 100 ton machine caused the breakage of two fastening screws of the concrete base. The equipment became tilted and some parts of the concrete were already showing the metal structure, causing their oxidation. It was necessary to recover the surface with a concrete repair product with excellent mechanical resistance.

PRODUCTS

Belzona 4111 (Magma Quartz)

Belzona 4911 (Magma TX Conditioner)

SUBSTRATE

Concrete and steel bar

APPLICATION METHOD

The application was carried out based on Belzona Know-How System Leaflet FPA-1. Surface was prepared with abrasive grit blast and wire brush. After that, the conditioner Belzona 4911 was applied on the concrete and Belzona 4111 was applied to fill out the damaged areas and to rebuild the corner of the base.

BELZONA FACTS

This application was completed successfully allowing quick return to service.

PICTURES

1. General view of the crusher
2. Crusher's base with exposed metal structure
3. Application of Belzona 4111
4. Crusher's base repaired with Belzona technology



1.



2.



3.



4.

For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

UK • USA • Canada • Thailand
www.belzona.com


BELZONA
Repair • Protect • Improve