

INTERNAL COATING FOR CENTRIFUGAL PUMP

CUSTOMER

Niagara, Ontario, Canada

APPLICATION DATE

September 2013

APPLICATION SITUATION

Centrifugal pump is used to transport fluids in the waste water treatment plant

PROBLEM

A customer wanted to protect and expand the life of a new pump due to installed at the plant to replace the existing pump which was suffering from corrosion/erosion due to sewage waste.

PRODUCTS

Belzona 1321 (Ceramic S-Metal)

Belzona 9111 (Cleaner Degreaser)

SUBSTRATE

Steel

APPLICATION METHOD

Application was carried out in accordance with Belzona Know-How System Leaflet CEP-3. The surface was prepared by grit blasting the entire surface to be coated, brushing away any loose contamination and washing the surface with Belzona 9111. Belzona 1321 was applied directly on to the prepared surface with a stiff bristle brush in accordance with the Belzona Instructions For Use.

BELZONA FACTS

Belzona 1321 will protect from abrasion and erosion - corrosion. This also has outstanding chemical resistance with high compressive strength and does not corrode. Belzona 1321 is designed to operate under continuous immersion at temperatures up to 140°F (60°C)

PICTURES

1. Centrifugal Pump Prior to Application
2. Preparation Complete
3. Application
4. Completed Application



1.



2.



3.



4.

For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

UK • USA • Canada • Thailand
www.belzona.com


BELZONA
Repair • Protect • Improve