

BELZONA PROTECTS CONCRETE FLOOR AGAINST OIL CONTAMINATION

CUSTOMER

Milton, ON, Canada

APPLICATION DATE

July 2013

APPLICATION SITUATION

Floor in an auction barn.

PROBLEM

The customer wanted to improve the look of the concrete floor and also avoid oil contamination from vehicles.

PRODUCTS

Belzona 5231 (SG Laminate)

SUBSTRATE

Concrete

APPLICATION METHOD

The application was carried out in accordance with Belzona Know-How System Leaflet FPA-3 for protecting floors and drains against chemical attack. A jet wash was used to clean the floor of any contamination and a diamond grinder was used to prepare the floor. Belzona 5231 was applied to the surface as a two coat system using a medium nap roller in accordance with the Belzona Instructions For Use.

BELZONA FACTS

The customer's decision to use Belzona 5231 was based on its high build, solvent free coating suitable for application to a range of rigid substrates including concrete and steel. Slip resistance can be improved by incorporating additional aggregate. This system is easily mixed and applied by using a roller. Downtime is minimal due to fast curing time.

PICTURES

1. Prior to application
2. Preparation in progress
3. Preparation in progress
4. Completed application



For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

UK • USA • Canada • Thailand
www.belzona.com


BELZONA®
Repair • Protect • Improve