BELZONA REPAIRS CAR PARK RAMP

CUSTOMER

Shopping centre, Bankstown, Australia

APPLICATION DATE

March 2004

APPLICATION SITUATION

Car park access ramp.

PROBLEM

Existing ramp concrete surface was badly damaged and expansion joint between the concrete slabs had deteriorated.

PRODUCTS

Belzona 4111 (Magma Quartz) Belzona 2221 (MP Fluid Elastomer)

SUBSTRATE

Concrete

APPLICATION METHOD

Application was carried out in accordance with the Belzona Know-How System leaflets FPA-1 and FPA-6. Existing ramp was removed by jackhammering and grinding and replaced with Belzona 4111. Existing expansion joint seal was removed and replaced with Belozna 2221 Elastomer.

BELZONA FACTS

High strength, impact resistant Belzona 4111 allowed ramp to be quickly and effectively restored. Belzona 2221 forms a highly elastic seal between the slabs.

PICTURES

- 1. The damaged ramp
- 2. Applying Belzona 4111 to the ramp
- 3. Pouring Belzona 2221 to seal the expansion joint
- 4. The completed ramp and expansion joint









For more examples of Belzona Know-How In Action, please visit http://khia.belzona.com



UK • USA • Canada • Thailand www.belzona.com

