

BELZONA PROTECTS ACID BUND AT CHEMICAL PLANT

CUSTOMER

Chemical plant, Kwinana, Western Australia

APPLICATION DATE

April 2016

APPLICATION SITUATION

Tanker loading/unloading station for 98% Sulphuric Acid.

PROBLEM

The concrete floor of the bund had been damaged by leaks during tanker deliveries.

PRODUCTS

Belzona 4111 (Magma Quartz)

Belzona 4311 (Magma CR1)

SUBSTRATE

Concrete

APPLICATION METHOD

Application was carried out in accordance with Belzona System Leaflet TCC-15. The floor of the bund was first washed to neutralise any remaining acid contamination before being abrasive blasted. Belzona 4111 used to rebuild damaged concrete before applying two coat system of Belzona 4311. Aggregate was applied to top surface whilst wet to create a non-slip surface.

BELZONA FACTS

Belzona 4000 series materials were chosen for their high chemical resistance, ability to bond to damaged concrete and fast curing properties that allowed for the application to be completed between deliveries, avoiding disruption to the operation of the plant.

PICTURES

1. Original condition of concrete before repair
2. Another view of the damage
3. Completed application
4. Another view of the completed application



For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

UK • USA • Canada • Thailand
www.belzona.com


BELZONA
Repair • Protect • Improve