

BELZONA REPAIRS FATTY ACIDS CONTAINMENT AREA

CUSTOMER

Specialty Chemicals Manufacturer, NC, USA

APPLICATION DATE

April 2015

APPLICATION SITUATION

Secondary containment area where fatty acids were stored.

PROBLEM

Concrete surfaces were severely corroded and eroded from leaking equipment.

PRODUCTS

Belzona 4154 (Bulkfill Resin)

Belzona 5811 (Immersion Grade)

Belzona 4181 (AHR Magma-Quartz)

SUBSTRATE

Concrete

APPLICATION METHOD

Old surfaces were pressure washed and any loose material was removed. The eroded concrete surfaces were resurfaced using Belzona 4154 mixed with sand. The surfaces were built up to original spec (up to 1.5 inches in some areas) and new gradients were created to ensure correct drainage. Belzona 4181 was used to repair the concrete directly under the steam lines. Two coats of Belzona 5811 were applied on the rebuilt surfaces. The application area was approximately 800 square feet.

BELZONA FACTS

The only other option was to have new concrete structures made. The repair took a total of 5 days. Belzona was chosen due to previous KHIA's showing containment repairs and short repair time.

PICTURES

1. Severely corroded and eroded concrete resulting from leaking equipment.
2. First part of the repair in contrast to the original condition. Belzona 4154 mixed with sand plus 2 coats of Belzona 5811. Draining rebuilt to eliminate ponding.
3. Closer look at the repair.



For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

UK • USA • Canada • Thailand
www.belzona.com


BELZONA
Repair • Protect • Improve