BELZONA OPTIMIZES THE EFFICIENCY OF A DISTRIBUTION CHAMBER

CUSTOMER

France

APPLICATION DATE

September/October 2013

APPLICATION SITUATION

Steel and concrete surfaces of a distribution chamber.

PROBLEM

Due to an important flowrate of water from the river nearby, the surface of this distribution chamber, which had not been protected before, was badly damaged and needed to be rebuilt. The sharp angles of the concrete inside the chamber cause a resistance to the water flow, besides, the steel surface is badly corroded.

PRODUCTS

Belzona 4111 (Magma-Quartz) Belzona 1341 (Supermetalglide)

SUBSTRATE

Concrete and Steel

APPLICATION METHOD

All the damaged parts of concrete were removed, then both substrates were grit blasted. The concrete substrate was rebuilt using Belzona 4111 using a modified version of Belzona Know-How System Leaflet FPA-1. Belzona 1341 was then applied on the steel and the concrete according to the Belzona Know-How System Leaflet CEP-10.

BELZONA FACTS

The customer was really satisfied with the application and observed an increase in the equipment efficiency.

PICTURES

- 1. Sharp angle on the concrete
- 2. Reconstruction of concrete
- 3. Application of Belzona 1341
- 4. Final application









For more examples of Belzona Know-How In Action, please visit http://khia.belzona.com



Belzona products are manufactured under an ISO 9000 Registered Quality Management System.

