

BELZONA PROTECTS OPERATORS IN A SUGAR REFINERY USING BELZONA 5871

CUSTOMER

L'Aube region of France

APPLICATION DATE

September 2020

APPLICATION SITUATION

Stainless steel pipework transporting steam at 90°C, is handled manually by operators when purging the system.

PROBLEM

Operator safety was a major concern for the asset owners, when their operators are having to manually operate the purge valves due to the pipework transporting steam at 90°C, therefore being a hazard and exposing the operators to potentials burn incidents. The internal micro-cavities obtained by the system as it expands, creates a high performance thermal barrier, insulating the thermal process and/or preserving the safety of the operators. The new contact temperature after using Belzona 5871 was 47°C.

PRODUCTS

Belzona 5871 Belzona 9111

SUBSTRATE

Stainless Steel - Grade 316

APPLICATION METHOD

The application was done in accordance with a modified version of Belzona's VPF System Leaflets. Belzona 5871 was manually applied using a brush no larger than 20mm wide, with the bristles cut down to 25mm. The product was applied to achieve a thickness of 6mm.

BELZONA FACTS


Alternatively they could have used conventional heat-insulation but much too expensive on small diameter pipework. Thanks to Belzona's innovation, there are no other similar products on the market making Belzona the best choice as a market leader.

PICTURES

1. Belzona 5871 Final System Backside near Walkway
2. Belzona 5871 Final System Backside near Walkway (Close-Up)
3. Belzona 5871 Final System Purge Valve Access



1.



2.



3.

For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>

ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve