

## BELZONA PROTECTS SCREW CONVEYOR AGAINST ABRASIVE ATTACK

### CUSTOMER

Biomass Plant, Glasgow, UK

### APPLICATION DATE

November 2019

### APPLICATION SITUATION

Screw conveyor used to skim sludge from the base of a silo at a biomass plant.

### PROBLEM

High abrasion was leading to unprotected screws only lasting 3-4 months in service. Previous Belzona applications on this type of screw was completed with Belzona 1812, which extended their life to over 2 years.

### PRODUCTS

Belzona 1814

### SUBSTRATE

Carbon Steel

### APPLICATION METHOD

The application was completed in accordance with system leaflet SHM-14. The screw conveyor was grit blasted to SA2 1/2 with a minimum surface profile of 3 mil (75 microns). The area to be coated was then cleaned and degreased using Belzona 9111. Belzona 1814 was applied by brush to the entire area of the conveyor to provide long-term protection against heavy abrasion.

### BELZONA FACTS

The client was keen to try Belzona 1814 on their latest screw conveyor as had previously had success with Belzona 1812 and wanted to see if this product could last the same amount of time in service.

### PICTURES

1. Close up of the material
2. Belzona 1814 applied
3. Unprotected screw conveyor



1.



2.



3.

For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>

ISO 9001:2008  
Q 09335  
ISO 14001:2004  
EMS 509612

Belzona products are  
manufactured under an ISO  
9000 Registered Quality  
Management System.

[www.belzona.com](http://www.belzona.com)

  
**BELZONA®**  
Repair • Protect • Improve