

BELZONA REPAIR BY ROPE ACCESS

CUSTOMER

Offshore Platform, Indonesia

APPLICATION DATE

August 2005

APPLICATION SITUATION

8-inch diameter Neoprene coated Riser Pipe

PROBLEM

Damage on Neoprene coating and corrosion in splash zone.

PRODUCTS

Belzona® 2211 (MP Hi-Build Elastomer)

Belzona® 2121 (D&A Hi-Coat Elastomer)

Belzona® 5831 (ST Barrier)

SUBSTRATE

Carbon steel and Neoprene

APPLICATION METHOD

Application carried out in accordance with modified Belzona Know-How System Leaflet VPF-3. Existing Neoprene repaired and coated with Belzona® 2211 and Belzona® 2121. Splash zone protected with Belzona® 5831.

BELZONA FACTS

Belzona systems chosen for their ease of application and Belzona® 5831 specifically for its surface tolerance and ability to cure in wet conditions.

PICTURES

1. Preparation of existing Neoprene
2. Rebuild and coating with Belzona® 2211 and Belzona® 2121
3. Coating splashing zone with Belzona® 5831
4. Complete application



For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



Belzona products are manufactured under an ISO 9000 Registered Quality Management System.

UK • USA • Canada • China
www.belzona.com

