

BELZONA REPAIRS AND COATS RUBBER SOCK

CUSTOMER

Richmond Hill, ON, Canada

APPLICATION DATE

September 2013

APPLICATION SITUATION

Rubber sock that dispenses concrete into the trucks.

PROBLEM

The rubber sock was worn.

PRODUCTS

Belzona 2211 (MP Hi-Build Elastomer)

Belzona 2221 (MP Fluid Elastomer)

Belzona 2311 (SR Elastomer)

Belzona 2911 (Elastomer QD Conditioner)

SUBSTRATE

Rubber

APPLICATION METHOD

The application was carried out in accordance with Belzona Know-How System Leaflet SHM-9 for creating and repairing rubber linings. The surface was prepared by removing any dirt or debris and cleaned. Belzona 2911 was applied to the prepared area and Belzona 2311 was applied with a brush. Belzona 2211 and Belzona 2221 were applied using a brush in accordance with Belzona Instructions For Use.

BELZONA FACTS

Belzona 2211 and Belzona 2221 are two-component elastomeric polymer repair composites for repairing and rebuilding rubber components. These versatile, high performance elastomers can be applied without the need for specialist tools and will bond strongly to a wide range of substrates including natural rubber, nitrile, neoprene, polyurethane, PVC, steel, copper, aluminum and concrete.

PICTURES

1. Rubber sock
2. Prior to application
3. Complete preparation
4. Completed application



1.



2.



3.



4.

For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



Belzona products are manufactured under an ISO 9000 Registered Quality Management System.

UK • USA • Canada • Thailand
www.belzona.com


BELZONA
Repair • Protect • Improve