

FLEXIBLE PROTECTION FOR ACID BUND WITH BELZONA

CUSTOMER

Power Plant, Missouri, USA

APPLICATION DATE

March 2015

APPLICATION SITUATION

Chemical Bund around 93% Sulfuric Acid Tank

PROBLEM

The bund in place to contain spillages from a 93% sulfuric acid tank experienced splashes and spills, resulting in the failure of existing protection. In addition, structural movement resulted in small gaps forming between the floor and bottom of the wall inside the containment area.

PRODUCTS

Belzona 4361

SUBSTRATE

Concrete

APPLICATION METHOD

The application was carried out in accordance with Belzona Know-How System Leaflet TCC-15.

BELZONA FACTS

After assessing the problem, the local Belzona Distributor proposed to use Belzona 4361 due to its excellent chemical resistance, flexibility and good adhesion, facilitating long-term sealing between the wall and the floor. The application was carried out in March 2015 and inspected after 9 months with Belzona protection fully intact.

PICTURES

1. Chemical Bund containing 93% Sulfuric Acid Tank
2. Belzona 4361 applied in two coats
3. Completed application



1.



2.



3.

For more examples of *Belzona Know-How In Action*, please visit <http://khia.belzona.com>



Belzona products are manufactured under an ISO 9000 Registered Quality Management System.

UK • USA • Canada • Thailand
www.belzona.com

