

BELZONA SEAL SURVIVES THE ACID TEST

ID: 1107

Industry: Chemical & Petrochemical Customer Location: Petrochemical Plant, Torun, Poland

Application: TCC-Tanks and Chemical Containment Application Date: June 2005

Areas

Substrate: Fibre Reinforced Composite, Steel

Products: * Belzona® 4181 (AHR Magma Quartz)Belzona® 4341 (Magma CR4),

Problem

The column operated with acids, trichloroacetic aldehyde, dichloroethane and trichloroethane at 20-100C and is protected by a graphite fibre reinforced laminate. This lining was additionally protected with acid proof bricks. In the first year of operation it emerged that there was no possibility of sealing the column manhole after opening during routine inspection, and a suitable protective system was needed.









Photograph Descriptions

- * The column situation ,
- * Installing acid resistant bricks with Belzona® 4181,
- * The completed Belzona® 4181 application,
- * The completed Belzona® 4341 application,

Application Situation

Process Column

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflet TCC-3. The internal lining was removed in both manhole areas. The first layer of protection used Belzona® 4181 in conjunction with acid resistant tiles. The flange faces were also protected with a lining of Belzona® 4181 composite additionally covered with Belzona® 4341 coating.

Belzona Facts

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com



 108 SHOWED THE BEIZOHA L	o be in perfect condition.	

EMS 695213

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality Management System.

