BELZONA ELIMINATES BREACHES IN BLAST FURNACE

ID: 1371

Industry: General Industry Customer Location: Steel Manufacturer, Teesside, UK

Application: MPT-Mechanical Power Transmission Application Date: October 2009

Substrate: Carbon Steel

Products: * Belzona® 1111 (Super Metal),

Problem

Abrasive dust and gases from the blast furnace had bypassed packings and seals around the shaft for the flow control gate at the top of the blast furnace. Damage had rapidly escalated, creating several grooved rings and severely gouged pits up to 15mm deep, allowing gases to escape, creating a potentially toxic area.









Photograph Descriptions

- * Blast Furnace Flow Control Gate assembled,
- * Damaged shaft,
- * Application of Belzona® 1111 and clamp former,
- * Final dressing of Belzona® 1111 before reassembly,

Application Situation

Shaft for the Flow Control Gate into the blast furnace.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflet MPT-2.

Belzona Facts

The contractor completed the work throughout the night and under a tight schedule. 9Kg of Belzona® 1111 was used with a purpose built clamp to recreate the original shaft profile of 280mm diameter. The preparation and application took only 2.5 hours, followed by a 5 hour cure period using heating pads to accelerate the cure. The blast furnace was returned to service with minimum downtime and to the complete satisfaction of the client.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA

www.helzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA