

BELZONA SIMPLIFIES REPAIRS IN GLASS LINED REACTORS

ID: 147

Industry: *General Industry*

Customer Location: *Chemical Fertilizer Plant in the Middle East*

Application: *TCC-Tanks and Chemical Containment Areas*

Application Date: *Ongoing since 1987*

Substrate: *Metal and Glass*

Products: ** Belzona® 1311 (Ceramic R-Metal) ,*

Problem

Damage to the glass lining caused by mis-handling of the covers and introduction of foreign bodies into the mixing process.



Photograph Descriptions

- * General view of the reactor ,
- * Typical damage to glass lining on cover ,
- * Repairs to cover being made. Note use of mixing board to form smooth surface on Belzona® 1311 ,
- * Local repairs with Belzona® 1311 to damaged glass protection on mixer shaft ,

Application Situation

Chemical Reactors operating at 120°C and 7 bar pressure.

Application Method

Application is carried out in accordance with Belzona Know How System Leaflet TCC-3.

Belzona Facts

The Belzona repair can be completed in three hours. Making and securing Tantalum patches can take several days. Belzona® 1311 is only viable repair on agitator, Tantalum patches cannot be secured.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015

Belzona products are

FS 695214

manufactured under an ISO

ISO 14001:2015

9000 Registered Quality

EMS 695213

Management System.

www.belzona.com

