

BELZONA GETS COMPRESSOR BACK TO SERVICE IN HOURS

ID: 1584

Industry: *Buildings & Structures*

Application: *CEP-Centrifugal Pumps*

Substrate: *Steel*

Products: ** Belzona® 1321 (Ceramic S-Metal) ,*

Customer Location: *Fertilizer producer, Hungary*

Application Date: *2010*

Problem

Worn compressors are unable to supply the necessary amount of CO2 into the production line.



Photograph Descriptions

- * Worn surface ,
- * Injecting Belzona® 1321 ,
- * Smooth finished surface after removing former ,
- * Finished compressor housing ,

Application Situation

CO2 compressor, a key equipment in producing Amide fertilizer.

Application Method

Application is carried out in accordance with a modified version of Belzona Know-How System Leaflet PDP-2 and MPT-2. Belzona® 1321 is injected into a stainless steel form prepared to match the required bore. It is treated with Belzona® 9411 (Release Agent) to aid removal once the Belzona® 1321 has cured.

Belzona Facts

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA®
Repair • Protect • Improve

Copyright © Belzona International Limited 2025

The cost of such an application is only a small fraction of a new equipment purchase. Another competitor had already failed because of its hand applied surface. Injecting Belzona® 1321 provides perfect and smooth surface within just a few hours.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

