# **Belzona Repairs Trip Hazards at Cider Factory**

ID: 1593

Industry: General Industry Customer Location: Cider Manufacturer, UK
Application: FPA-Floor Problem Areas Application Date: December 2008

Substrate: Concrete

Products: \* Belzona® 4911 (Magma TX Conditioner),

\* Belzona® 4131 (Magma Screed),

#### Problem

There are access lids at the base of the tank which are held in place with bolts and secured by a gasket to the base of the lid. However, these areas can be prone to leaking as the aggressive cider juice drips and eats away at the gasket and then attacks the concrete floor at the base of the tank, as you can see from the pictures. Eventually, this creates a gulley which can be a serious trip hazard.









## **Photograph Descriptions**

- \* The grooves in the floor,
- \* Applying the Belzona® 4131 by hand,
- \* Filling in the gaps by hand,
- \* The old and new floor, viewed at ground level ,

## **Application Situation**

Repairs to floor

## **Application Method**

The areas requiring repair were washed down. As per the IFU once dry the areas were coated with Belzona® 4911 followed by Belzona® 4131. We discovered that the process worked best when applied by (gloved) hand whilst holding the trowel against the

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA

concrete edge and sliding the trowel away once the Belzona® 4131 was in the void.

#### **Belzona Facts**

After a first inspection over a month later, the surrounding area was discoulouring and graining but the reclaimed areas were standing up well to exposure to the raw cider. As a result, the client now wishes to coat the whole area once the application has proved itself, as well as the other eight 'planetary suites.