STEEL PLANT NOW BACK ON LINE WITH BELZONA WRAP

ID: 2197

Industry: General Industry Customer Location: Steel Plant, Teesside, UK

Application: VPF-Valves, Pipes and Fittings Application Date: 2011

Substrate: Cast Iron

Products: * Belzona® 1121 (Super XL Metal),

* Belzona® 9341 (Reinforcing Tape),

Problem

The gas leak on the cast iron pipe was detected and once excavated a 10 inch long crack over the socket area was found to be the cause. The pipe was critical to the plant operation so an immediate solution was required. The coke oven gas had a typical internal pressure of 500 mbar and client needed to reduce the repair period to a minimum.







Photograph Descriptions

- * Site access to excavated pipe section,
- * Excavated 24 inch Gas Main with crack identified,
- * Completed Belzona® 1121 wrap,

Application Situation

Leaking 24 inch cast iron coke oven gas main from the coke ovens to the power plant .

Application Method

The crack was terminated and vee'd cut in accordance with Belzona Know-How System Leaflet VPF-8. Belzona® 1121 was used to pack the gasket and create fillets on either side of the flange, before conducting a wrap repair in accordance with Belzona Know-How System Leaflet VPF-11a.

Belzona Facts

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA

The client asked Belzona for a rapid response and the preparation and application were completed within a day. Because of the restricted access in the pit and the size of the pipe, Belzona® 1121 was chosen to conduct the repair throughout due to its longer working life. The external pipe diameters were nominally 67cm, with a flange of 83cm diameter. The final 3 layer wrap was approximately 97cm length, and consumed 96Kg of Belzona® 1121. After curing for a day the gas main was reopened and tested at full pressure to the absolute satisfaction of the client.

