BELZONA RESTORES FLOTATION UNIT AT BIOMASS PLANT

ID: 5470

Industry: General Industry Customer Location: Pharmaceutical Company, Ayrshire, UK

Application: TCC-Tanks and Chemical Containment Application Date: August 2014

Areas

Substrate: Stainless Steel 304L

Products: * Belzona 1111 (Super Metal),


* Belzona 5892,

Problem

Severe pitting corrosion to the stainless steel unit caused by Ferric Chloride.









Photograph Descriptions

- * DAF unit,
- * Pitting Corrosion,
- * Plate bonding,
- * Completed Application,

Application Situation

Dissolved Air Flotation (DAF) Unit in Biomass Plant

Application Method

The application was carried out in accordance with TCC-1 and TCC-3. Belzona 1111 was used to rebuild the pitting damage. In deeply pitted areas doubler plates were bonded into place. Afterwards the full tank was lined with Belzona 5892.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA

Belzona Facts The application from start to finish including surface preparation lasted just 3 weeks. While the DAF was down the plant was running at 50% of its capacity therefore the quick turnaround time was very beneficial to the customer.