# BELZONA BONDS RISER BEARINGS ON OFFSHORE PLATFORM

ID: 5539

Industry: Oil & Gas Customer Location: Rig Fabricator, South Korea

Application: GSS-Gaskets, Seals and Shims Application Date: 2014

Substrate: Carbon Steel and Super Duplex Stainless Steel

Products: \* Belzona 1111 (Super Metal) , \* Belzona 1321 (Ceramic S-Metal) ,

#### **Problem**

When stationed, Risers move inside the housings, creating abrasion and exacerbating corrosion. The decision was made to protect these areas with composite bearings. As the Bearings reached 2.5m diameter and 3m length they were split into (up to 16) sections and had to be bonded in place. A total of 84 risers and housings were completed on the hullside and 27 on the topside.









## **Photograph Descriptions**

- \* Fitting Bearing to Housing,
- \* Fitting Bearing to Riser,
- \* Injecting Belzona 1321,
- \* Riser inserted into Housing,

## **Application Situation**

Risers and Riser housings needed protection on a new build Central Processing Facility.

### **Application Method**

The application was carried out in accordance with Belzona Know-How System Leaflet GSS-9. The Bearings were aligned in place using jigs, straps and injection port bolts. The Bearing had to be jacked to 4mm from the substrate. The seams were then dammed

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA

using Belzona 1111. Belzona 1321 was injected through the injection ports. After curing the injection ports were cut off, filled with Belzona 1111, and ground flush.

### **Belzona Facts**

The Central Processing Facility required the highest performance product available as they had a design life of 40 years. Belzona was able to offer the products and technical support to design and support the installation of the liners.

www.belzona.com