

BELZONA REPLACES PTFE LINING AND CUTS DOWNTIME

ID: 5655

Industry: Chemical & Petrochemical
 Application: TCC-Tanks and Chemical Containment Areas
 Substrate: Steel
 Products: * Belzona 1593 ,

Customer Location: Chemical Plant, Ferrara, Italy
 Application Date: April, 2015

Problem

The original hot applied PTFE Lining required maintenance due to localised disbondment. The plant was facing a long downtime as it was not possible to conduct an in-situ repair of such a lining. The customer was looking for a solution that was faster and easier to apply.



Photograph Descriptions

- * PTFE lining removed ,
- * Belzona lining applied ,
- * Coating thickness measured ,
- * Inspected after 6 months in service ,

Application Situation

Reactor operating between 70°C and 80°C at a Polyolefins petrochemical plant. Process fluids included salt, caustic and titanium tetrachloride.

Application Method

The application was carried out in accordance with Belzona Know-How System Leaflet TCC-5 for protecting and rebuilding steelwork. After grit blasting to SA 2.5, a two-coat system of Belzona 1593 was hand applied to an area of 25 m².

Belzona Facts

Belzona was chosen to replace PTFE as it reduced downtime from weeks to days and was also much easier to apply. Any future

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
 FS 695214
 ISO 14001:2015
 EMS 695213

Belzona products are
 manufactured under an ISO
 9000 Registered Quality
 Management System.

www.belzona.com


BELZONA[®]
 Repair • Protect • Improve

mechanical damage will be repairable in-situ.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015	Belzona products are
FS 695214	manufactured under an ISO
ISO 14001:2015	9000 Registered Quality
EMS 695213	Management System.

www.belzona.com

