LOCALIZED BELZONA REPAIRS TO RUBBER LININGS

ID: 6060

Industry: Power Customer Location: Power Plant, UK

Application: TCC-Tanks and Chemical Containment Application Date: 2007

Areas

Substrate: Carbon steel with 6mm neoprene rubber lining.

Products: * Belzona 2111 (D & A Hi-Build Elastomer),

* Belzona 2911 (Elastomer QD Conditioner),

Problem

The client had recurring failures of the aged neoprene rubber linings on the site. Reinstatement or repairs with the original lining materials were impossible due to unacceptable downtime and health & safety concerns. A localised repair solution was needed that could be easily applied in confined spaces to complex surfaces, and would allow a fast return to service.









Photograph Descriptions

- * Defect areas marked up in a water treatment tank,
- * Failed neoprene rubber lining being removed,
- * Completed repairs with Belzona 2111,
- * Further repairs completed on tank walls,

Application Situation

Existing rubber linings in tanks and vessels needing repair.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflet TCC-3. After preparing the substrate, Belzona 2911 was applied before repairing the rubber lining with Belzona 2111.

Belzona Facts

The customer has been using these Belzona liquid applied elastomers across the site now since 2007, with thousands of repairs being completed on their tank linings. Belzona 2911 ensures optimum adhesion to the substrate and is dry in as little as 30 minutes.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA®

ws the repairs to be completed		