

BELZONA REBUILDS AND PROTECTS TURBINE RUNNER

ID: 6071

Industry: Power
Application: CEP-Centrifugal Pumps
Substrate: Cast iron
Products: * Belzona 1311 (Ceramic R-Metal) ,
* Belzona 1321 (Ceramic S-Metal) ,

Customer Location: Hydroelectric Plant, Jokkmokk, Sweden
Application Date: 2014

Problem

Constant use had damaged the vulnerable cast iron substrate of the impellers. The client needed a quick, long-term solution to avoid downtime to their plant.



Photograph Descriptions

- * Turbine housing entrance ,
- * Cavitation damage to the runner ,
- * Close-up of the damage ,
- * Completed application ,

Application Situation

Two impeller runner blades had suffered severe cavitation and erosion damage.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflets CEP-1 and CEP-3. Surfaces were grit blasted prior to rebuilding with Belzona 1311 to restore profiles and coating with Belzona 1321 to provide long-term protection.

Belzona Facts

The Belzona solution is cold-applied and simple to use, which meant that repairs and the application could be performed in-situ, avoiding costly disassembly work which would force a long downtime period. Force curing Belzona allowed the plant to return to operational status as quickly as possible, whilst the Belzona application offers a long-term, durable solution.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA[®]
Repair • Protect • Improve