## BELZONA SEAMLESS ROOFING FOR SUBSTATIONS

ID: 6109

Industry:Chemical & PetrochemicalCustomer Location: Refinery, UKApplication:RPA-Roof Problem AreasApplication Date: 2009

Substrate: De-chipped asphalt
Products: \*Belzona 4141 (Magma-Build) ,

\* Belzona 3131 (WG Membrane) ,

#### **Problem**

Leaks in problem areas of the substation roofs were concerning management due to the potential to shutdown large sections of the plant. These flat roofs were typically 30 years old and previously protected with asphalt or bitumen felt. Tests with alternative roofing systems had not provided adequate protection due to not being ideally suited to sealing complex areas such as vents.









## **Photograph Descriptions**

- \* Substation flat roof,
- \* Asphalt de-chipped,
- \* New vent detail of finished system,
- \* Completed roof fully protected with Belzona 3131,

### **Application Situation**

Flat asphalt roofs over plant electrical substations. The roof illustrated here was the first of many refurbished on site and comprised 18mm chippings over an asphalt deck totalling 260 square meters with extensive lichen and moss growth.

# **Application Method**

Application was carried out in accordance with Belzona Know-How System Leaflets RPA-1, RPA-2, RPA-6, RPA-8, RPA-10 and RPA-11 to address the many different situations.

#### **Belzona Facts**

The client's biggest concern was that failure of the roofing would result in significant safety and operational problems due to the

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®

www.helzona.com

high voltage electrical equipment. The roof was fully reinforced to create a completely seamless membrane that offers over 20 years durability. The Winter Grade system proved to be a real advantage whilst applying the materials during the typically wet UK weather. During 2009, 14 substation roofs totalling over 2200 square meters were protected with applications continuing throughout the winter months.

