BELZONA REBUILDS THE WALLS OF A SECONDARY CONTAINMENT AREA

ID: 6115

Industry: Buildings & Structures Customer Location: Cement Plant, Oregon, USA

Application: WPA-Wall Problem Areas Application Date: September 2015

Products: * Belzona 4111 (Magma-Quartz),

Concrete and steel rebar

* Belzona 4154 (Bulkfill Resin),

* Belzona 4911 (Magma TX Conditioner),

Problem

Substrate:

Severe cracks and damage in the walls of the ammonia secondary containment due to design issues.









Photograph Descriptions

- * Showing damage to the walls,
- * Forming boards used for the application of Belzona 4154,
- * Pouring of Belzona 4154,
- * Completed application showing Belzona 4111 as a top layer,

Application Situation

Concrete walls of an ammonia secondary containment area.

Application Method

The damage at the SE corner required cutting out a section of the walls in one area and a simple removal of a small section at the SW corner. A grinder was used to remove oxidation from rebar. Belzona 4911 was applied to the steel rebar and concrete. Form boards were attached to the concrete to create a frame before pouring Belzona 4154. Once cured, the form boards were removed. A grinder was used to remove the gloss off of Belzona 4154, then the surface was wetted with Belzona 4911 to prepare it for the application of Belzona 4111 as a finishing layer.

Belzona Facts

Originally the plan called for rebuilding with concrete. When the engineers saw the bond strength of the Belzona 4154 and 4111

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

they decided Belzona would work much better.		