# **Belzona Repairs and Protects Screw conveyor**

ID: 6459

Industry: Water / Wastewater Customer Location: Wastewater Treatment Plant, Bialystok

**Poland** 

Application: SHM-Solids Handling Machinery Application Date: July 2014

Substrate: Steel

Products: \* Belzona 1511 (Super HT-Metal),

\* Belzona 9811 , \* Belzona 1813 ,

#### **Problem**

The new screw conveyor suffered surprisingly fast wear by erosion and bi-metallic corrosion. The shaft of the screw conveyor had been topped with a stainless steel sheet to protect it from corrosion. However, after less than a year of operation the steel was worn from the surface of the shaft. In addition to the aggression of chemical sludge, it reaches a very high temperature of approx. 120 degrees Celsius.









## **Photograph Descriptions**

- \* 1.Screw conveyor before application,
- \* 2. Visible effects of galvanic corrosion,
- \* 3.Application of Belzona 9811 and Belzona 1511,
- \* 4.View after grouting with Belzona 1813,

## **Application Situation**

Sludge screw conveyor.

# **Application Method**

The application was carried out in accordance with Belzona System leaflet SHM-14. The surface of the shaft was blasted and Belzona 9811 tiles were bonded to the surface of the shaft using Belzona 1511. The tiles were grouted using Belzona 1813.

### **Belzona Facts**

The Belzona solution eliminated the problem of galvanic corrosion and increased the durability of the screw conveyor. With Belzona

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com



the life time is three times longer than the original solution.	