

BELZONA PROTECTS 10,000 SQUARE FEET OF FLOORING

ID: 69

Industry: Chemical & Petrochemical
Application: TCC-Tanks and Chemical Containment Areas
Substrate: Concrete
Products: * Belzona® 5811 (Immersion Grade) ,
* Belzona® 2131 (D&A Fluid Elastomer) ,

Customer Location: Chemical Plant in Alabama
Application Date: December 1996

Problem

The chemical plant needed to prevent mercury from entering the ground through the concrete containment. The situation was aggravated by 50% KOH (potassium hydroxide) that was attacking the concrete and expansion joint sealant.



Photograph Descriptions

- * Bridging over expansion joint in accordance with modified Belzona application procedure TCC-12 with Belzona® 2131. ,
- * First coat of Belzona® 5811 applied with Belzona® 9221 (Surefoot Aggregate White) broadcast for non-skid safety system. Application of second coat Belzona® 5811 (tinted red) in progress. ,
- * The completed application, floor and ground protected from chemical degradation and contamination. ,

Application Situation

Chemical plant floor

Application Method

The application was carried out in accordance with Belzona Know-How Leaflets TCC-12 and TCC-15.

Belzona Facts

Not only was the floor protected from chemical attack, the customer prevented heavy EPA fines and mercury ground contamination.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA®
Repair • Protect • Improve