Belzona Repairs Turbine Exhaust Manifold

ID: 7561

Industry: Oil & Gas Customer Location: Oil Field Operator, North Sea Norway

Application: VPF-Valves, Pipes and Fittings Application Date: July 2013

Substrate: Carbon Steel

Products: * Belzona 1511 (HT Metal),

Problem

Due to severe corrosion these pipes were leaking exhaust gases in an area close to personell gangways creating a safety hazard. Temperatures in the area reached 200 C.









Photograph Descriptions

- * 1. View of corroded area with through wall defect.,
- * 2. Surface preparation carried out.,
- * 3. Metal plate bonded in position,
- * 4. Completed application,

Application Situation

Exhaust manifold piping.

Application Method

Application was carried out in accordance with Belzona System Leaflet VPF-11. A thin plate was bonded to cover the defect area and to prevent ingress of product during application. Two consecutive layers of Belzona 1511 HT Metal reinforced with Belzona 9341 were applied leaving a solid composite wrap of 20mm thickness.

Belzona Facts

Due to exhaust leaks close to personell gangways, the customer required a fast and effective solution to prevent the gases escaping until the next planned shut-down. The in-situ nature of the Belzona repair allowed this to be done quickly and efficiently saving the customer an unplanned shut-down to replace the pipe.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve