Belzona Rebuilds and Protects a Sulphuric Acid Tank

ID: 7900

Industry: General Industry Customer Location: France
Application: TCC-Tanks and Chemical Containment Application Date: 2017

Areas

Substrate: Mild Steel

Products: * Belzona 1121 (Super XL-Metal),

* Belzona 4311 (Magma CR1),

Problem

Due to the high concentration of sulphuric acid contained in this storage tank (98%), the walls were severely corroded, causing an unn loss of thickness.









Photograph Descriptions

- * Before surface preparation,
- * After surface preparation ,
- * Final application,
- * Final application,

Application Situation

Corrosion on the internal side of a storage tank containing sulphuric acid.

Application Method

The inside of the tank was first grit blasted, then Belzona 1121 was used to recover the loss of thickness. Then Belzona 4311 was used to protect the whole internal surface of the tank against sulphuric acid. This application was carried out in accordance with a modified version of Belzona Kow-How System Leaflet TCC-05.

Belzona Facts

The benefit for the customer here was the long-term protection against an aggressive chemical which would eventually cause the tank to leak.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®
Repair • Protect • Improve

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA