

# Belzona alters yacht window frames with ease

ID: 7949

Industry: Marine  
Application: GSS-Gaskets, Seals and Shims  
Substrate: Steel  
Products: \* Belzona 1121 ,

Customer Location: Mallorca  
Application Date: June 2018

## Problem

Due to a last minute design change affecting the thickness of the installed glass, the window frames had to be modified. As the structure had already been built, it was not possible to alter the structural design, and therefore an after market alteration had to be made so that the window frames could accommodate the lower thickness windows.



## Photograph Descriptions

- \* 1. General view of window frames ,
- \* 2. Surface being prepared for application ,
- \* 3. Belzona applied with formers in place ,
- \* 4. Completed application ,

## Application Situation

A newly built yacht window installation without 216 linear meters of window frame.

## Application Method

The application was carried out in accordance with a modified version of Belzona System Leaflet GSS-9. Belzona 1121 was used to build up the thickness of the window frames by 1 - 1.5 cm. A forming technique was used to ensure precise tolerances. Belzona 9411 (Release Agent) was applied to the formers so that they could be easily removed after the Belzona 1121 had cured.

## Belzona Facts

Belzona 1121 was selected due to its high build capability, allowing the required thickness to be added to the window frames in a single application. The Belzona material is 100% solids, meaning that it will not distort or shrink whilst curing. This is essential to ensure the correct tolerances can be met. Welding was considered, but rejected as it was deemed the heat stresses could damage

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015  
FS 695214  
ISO 14001:2015  
EMS 695213

Belzona products are  
manufactured under an ISO  
9000 Registered Quality  
Management System.

[www.belzona.com](http://www.belzona.com)



and distort the structural steel. Competitor products did not have the slump resistance to achieve the required thickness at one time, meaning the application would have been much more time consuming.

---

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015  
FS 695214  
ISO 14001:2015  
EMS 695213

Belzona products are  
manufactured under an ISO  
9000 Registered Quality  
Management System.

[www.belzona.com](http://www.belzona.com)

