

BELZONA CREATES POSITIVE GRIP ON RUBBER CLAD CONVEYOR DRIVE ROLL

ID: 7965


Industry: Mining & Quarrying
Application: SHM-Solids Handling Machinery

Customer Location: Zagreb, Croatia
Application Date: April 2014

Substrate: Rubber
Products: * Belzona 2111 (D&A Hi-Build Elastomer) ,
* Belzona 2911 (Elastomer QD Conditioner) ,
* Belzona 9211 (Supergrip Aggregate) ,

Problem

Worn rubber cladding was allowing belt slippage on a floating conveyor system used for transporting gravel. Whenever it happened on one of the rollers, the whole system would stop and it takes 30 minutes to restart it back to operating at full service. In rainy periods of the year this happens often and it is a significant loss of production time. Customer should also have spare rollers in stock ready for immediate installation.



Photograph Descriptions

- * 1. Floating conveyor systems used for transporting gravel ,
- * 2. Worn out rubber cladding ,
- * 3. Preparing for the installation of Belzona 2111 ,
- * 4. Fully applied system ,

Application Situation

Anti-slip chevron strips were applied directly onto an existing worn rubber lining of a conveyor drive roller. This was done without removing the lining and without dismantling the roller.

Application Method

Application was carried out in accordance with Belzona Know-How system leaflet SHM-9. Repair was carried out on site, during

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve

planned downtime of the plant. The conveyor belt was removed 10 cm away from the roller so that the roller could be rotated manually during the application, without touching the belt. Surface preparation was completed with a rotary wire brush and Belzona hand tools for the rubber. Next, chevron strips were marked with masking tape and the surface was conditioned with Belzona 2911. Finally, Belzona 2111 was brush applied and Belzona 9211 was incorporated into the material.

Belzona Facts

The benefit for the customer was avoiding the dismantling and transportation of rollers to the shore and also avoiding use of the stock of lined rollers. Removal of existing worn rubber lining and installing a new one must be completed by other contractors, which takes time and money. Application took 3 hours with Belzona and 24 hours for the Belzona 2111 to cure.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

