

BELZONA 5871 PROTECTS STEAM PIPING HAZARDOUS TO OPERATORS




ID: 8288

Industry: Pulp & Paper
Application: VPF-Valves, Pipes and Fittings
Substrate: Steel
Products: * Belzona 5871 ,

Customer Location: Alabama, USA
Application Date: May, 2020

Problem

These piping sections were a potential hazard for contact burn injuries since they are located at ground level.



Photograph Descriptions

- * Pipe coated with Belzona 5871 ,
- * Pipe coated with Belzona 5871 ,
- * Measuring temperature after application of Belzona 5871 ,
- * Measuring temperature after application of Belzona 5871 ,

Application Situation

Steam piping of four identical sections of a batch digester at a local paper mill, operating at 200°F max.

Application Method

The line was shut down for safety handling during application procedure. Belzona 5871 was applied in 4 coats in one day, with a total DFT of 160-180 mils.

Belzona Facts

The curing time of Belzona 5871 was accelerated because the pipe was still warm during application. All 4 layers of Belzona 5871

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com



were applied in one day, and 4 more identical pipe sections were repaired during a planned maintenance. Belzona was able to reduce the temperature down to 110F, preventing any type of contact surface burn and protecting the pipe against future corrosion degradation.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

