

Applying Belzona Coating For Internal Surface Of Media Filters

ID: 8406

Industry: *General Industry*
Application: *TCC-Tanks and Chemical Containment Areas*
Substrate: *Carbon Steel*
Products: ** Belzona 5821 ,*

Customer Location: *Egypt, Ain Sokhna*
Application Date: *October 2020*

Problem

Protect the media filters from erosion-corrosion



Photograph Descriptions

- * 1. General view of the filters. ,
- * 2. Surface before preparation. ,
- * 3. Filter internals after coating. ,
- * 4. Accesories were also protected. ,

Application Situation

Belzona coating for the new fabricated huge media filters

Application Method

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA®
Repair • Protect • Improve

1-Grit blasting the surface to the Swedish standard (SA 2 1/2) to give surface profile not less than 75 microns. 2-All surfaces shall then be degreased using a suitable cleaner-degreaser, which does not have a residue, such as MEK Methyl Ethyl Ketone (Non-residue chemical cleaner). 3-Apply two coating system of Belzona 5821 with dry film thickness 500 microns.

Belzona Facts

Belzona performed ultimate long term protection to the filters. This is a typical Belzona immersion protection application.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

