BELZONA SUPERWRAP II EXTENDS LIFE OF PIPING BY 10 YEARS

ID: 8574

Industry: Oil & Gas Customer Location: Western Australia
Application: VPF-Valves, Pipes and Fittings Application Date: October 2020

Substrate: Carbon Steel

Products: * Belzona 1983 (SuperWrap II Resin),

* Belzona 9381 (SuperWrap II Reinforcement Sheet),

* Belzona 9382 (Release Film),

Problem

The 250 mm diameter pipe had developed a critical (Class 3) through wall defect at the bent. The operating temperature was 50°C and the operating pressure was 15 bar.









Photograph Descriptions

- * 1. Defect area of the pipe,
- * 2. Surface abrasive blasted,
- * 3. Application in progress,
- * 4. Release Film over the wrap waiting to cure,

Application Situation

High Pressure, Fuel Oil Piping

Application Method

The application was completed in accordance with Belzona Know-How System Leaflet VPF-11. The defect area was abrasive blasted to SA 2.5 with a 75 microns profile. Belzona SuperWrap II was applied in accordance with the engineered design as an 8 wrap system with the total length of 490 mm, using Belzona 1983 resin to provide a further 12 years service life.

Belzona Facts

Belzona SuperWrap II was chosen because it is an engineered solution that can be designed as a pipe repair system being compliant to ISO 24817 and ASME PCC-2. With the customer being able to do their own designs and having validated applicators on site, makes the onsite maintenance team independent and the repair was completed with-in 48 hours.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA