

BELZONA SOLVES BALANCE PROBLEM ON IMPELLER

ID: 864

Industry: Oil & Gas
Application: GSS-Gaskets, Seals and Shims
Substrate: Bronze
Products: Belzona® 1321 (Ceramic S-Metal)

Customer Location: ConocoPhillips Refinery, Wood River, IL
Application Date: July 2007

Problem

Liquid slowly entered the void during operation causing an imbalance and vibration.



Photograph Descriptions

* General view of the impeller , * Injection port fitted , * Injection underway , * Vent port filled after injection completed ,

Application Situation

Impeller did not have a solid center bore. Instead, it had a boss fit on both sides with a 60 cubic inch void in the center.

Application Method

Belzona® 1321 was injected into the void, filling it completely. Application followed Belzona Know-How System Leaflet GSS-9

Belzona Facts

Belzona® 1321 extensively used for injecting irregular shims. Product has good handling characteristics, is non-shrinking and has high mechanical strength. The pump needed to be back in production, a new impeller would take 6 month to be delivered, then, more of the same was likely to occur!

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA®
Repair • Protect • Improve

Copyright © Belzona International Limited 2025