

# TOWBOAT FENDER REPAIR

ID: 8939

Industry: Marine  
Application: SOS-Ships and Offshore Structures


Customer Location: SEATTLE, WA, UNITED STATES  
Application Date: June 2022

Substrate: Rubber  
Products: Belzona 2221 (MP Fluid Elastomer), Belzona 2911 (Elastomer QD Conditioner)

Problem  
INTERLOCKING FENDER DELAMINATED.



INTERLOCKING FENDER SEAM  
SEPARATED.



PREPARING THE SUBSTRATE.



ATTACHING FORM.



COMPLETED REPAIR.

## Application Situation

FENDER COULD NOT BE REMOVED BY SHIPYARD TO REAPPLY TRADITIONAL ADHESIVE. TIME WAS CRITICAL TO THE SALE OF THE NEW VESSEL.

## Application Method

SUBSTRATE WAS PREPPED USING LONG SHAFTED DIE GRINDER.

SS SCREWS WERE INSTALLED AS ANCHOR POINTS.

## Belzona Facts

CUSTOMER NEEDED A LOCAL SOLUTION VERSUS RETURNING TO THE HOME PORT OF THE MANUFACTURER. REMOVAL OF THE FENDER SYSEM REQUIRES 2 CRANES AND A LARGE AREA. THIS REPAIR WAS HANDLED WITH MINIMAL IMPACT.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015  
FS 695214  
ISO 14001:2015  
EMS 695213

Belzona products are  
manufactured under an ISO  
9000 Registered Quality  
Management System.

[www.belzona.com](http://www.belzona.com)

