ACID CONTAINMENT FLOOR RE-HAB WITH BELZONA

ID: 903

Industry: Buildings & Structures Customer Location: Water Treatment Plant, OK

Application: FPA-Floor Problem Areas Application Date: July 2007

Substrate: Concrete

Products: * Belzona® 5811 (Immersion Grade),

* Belzona® 9541 (Bulkfill),

* Belzona® 9221 (Surefoot Aggregate),

Problem

Caustic and Fluoride spills due to pump leaks had eaten through the floor coating, down to the aggregate in some places, and destroyed the metal framework for the access way into the sump below. Previous coating failed and presented a slippery floor when hosed down.









Photograph Descriptions

- * Floor prepared for re-surfacing,
- * Re-shaping the access opening Belzona® 5811 ,
- * Grey coat over beige with Surefoot added ,
- * Rebuilt, protected, a first class job!,

Application Situation

Floor and sump access-way in water treatment plant.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflets FPA-1 & 3. Bulkfill was used to rebuild the sump access and spalled areas. The entire area was then given two coats of Immersion Grade with Surefoot Aggregate applied to achieve safe footing.

Belzona Facts

Local concrete repair services quoted the turnkey project excessively high. Maintenance staff with supervision were more than capable of carrying out the work. In the end, client saved taxpayer money, solved their own problem, on their own schedule and

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®

www.helzona.com

as tested, by the city to their satisfaction with the two acids.	