

Belzona protects cooling water pump's impeller from cavitation in nuclear power plant

ID: 9060

Industry: Power
Application: CEP-Centrifugal Pumps
Substrate: Stainless-steel
Products: Belzona 1111 (Super Metal), Belzona 1341 (Supermetalglide), Belzona 2141 (ACR-Fluid Elastomer)

Customer Location: Krško
Application Date:

Problem

At the end of planed overhaul, severe cavitation was detected on one of the main cooling pumps.



Cavitation damage



Rebuilding the damaged surface



Coating the surface



Finished application

Application Situation

Belzona distributor stepped up with a cost effective solution that would rebuild and protect the pump from further cavitation while providing efficiency enhancement to the pumps impeller. The repair and protection was completed in 4 days.

Application Method

The pump's impeller was grit blasted according to standard stated in the instructions for use.

Cavitation damage was rebuilt to profile with Belzona 1111.

Whole surface was protected with efficiency enhancement protective coating Belzona 1341.

Cavitation impact zones were coated with Belzona 2141 elastomer that can withstand cavitation.

Belzona Facts

There was no time for replacement and welding was not an option for it would distort impeller's hydrodynamics. Belzona saved the nuclear power plant company from additional downtime which would result in costly problems.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve