

FLANGE & FASTENINGS LEAKAGE

ID: 9381

Industry:	Chemical & Petrochemical	Customer Location:	Warrington UK
Application:	GSS-Gaskets, Seals and Shims	Application Date:	April 2024
Substrate:	Carbon steel		
Products:	Belzona 1511 (Super HT-Metal), Belzona 5811 (Immersion Grade)		

Problem

High temperature steam leaks and loss of vacuum at the interface of the two mating flanges



Condition of vessel circumferential flange



Surface preparation by grit blasting



Bolt caps filled with Belzona 1511 and general filling of flange interface.



Finally full encapsulation of repairs using Belzona 5811

Application Situation

This vessel was no longer operational and costing the company excessive amounts of extra turnover to move production to other parts of the plant

Application Method

Hi-Pressure Grit blast of all fastenings and flange face creating a good profile for adhesion to the substrate.

Belzona Facts

This facility uses Belzona products on machinery and equipment throughout the plant, the plant is old and invariably no spares available or very long lead times. Belzona is used on varying circumstances saving the plant downtime.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

