

Belzona SuperWrap application on ammonia pipes


ID: 9441

Industry: Chemical & Petrochemical
Application: VPF-Valves, Pipes and Fittings
Substrate: Carbon steel
Products: Belzona 1121 (Super XL-Metal), Belzona 1982 (SuperWrap II), Belzona 5811 (Immersion Grade)

Customer Location: Spain
Application Date: July

Problem

Belzona Superwrap II structural reinforcement system, under ASME PCC-2 standard, for 20 meters of buried pipe. This particular pipe was carrying ammonia. The pipe was experiencing pitting and wear and tear.



Corroded pipe used to carry ammonia.



Pipe during surface preparation.



The pipe is encapsulated with Belzona SuperWrap II.



The repaired pipe overcoated with Belzona 5811

Application Situation

The client has a large number of ammonia lines whose use is continuous, with the impossibility of stopping to replace sections of pipes with corrosion problems.

Application Method

The product was applied according to its respective Instructions for Use and leaflet documentation.

Belzona Facts

The client was largely interested in the speed of installation, the fact that the pipe did not have to be depressurized or made inert, and the warranty offered.

All documentation we have was sent through the BEL, emphasizing the key benefits of Superwrap II. We had direct contact with clients/presentations/meetings.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve