BELZONA REPAIRS AND PROTECTS SULPHURIC ACID BUND

ID: 963

Industry: Power Customer Location: Power Station, UK
Application: TCC-Tanks and Chemical Containment Application Date: December 2007

Areas

Substrate: Concrete

Products: * Belzona® 4311 (Magma CR1),

* Belzona® 4111 (Magma Quartz),

Problem

Malfunction in the system caused a quantity of 98% Acid to be dropped, followed by a quantity of distilled water. The resultant exothermic reaction was so rapid it stripped the original coating off the concrete substrate throughout the containment area.









Photograph Descriptions

- * Damaged tank pad,
- * Rebuilding with Belzona® 4111,
- * Rebuilding complete,
- * Tank pad protected with Belzona® 4311,

Application Situation

Secondary containment for two acid tanks in the water treatment section. The top tank contains 98% Sulphuric Acid that feeds into a lower tank diluted to 10% strength, and used in the water treatment process.

Application Method

Application was carried out in accordance with Belzona Know-How System Leaflets TCC-9 and TCC-15.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA®

٥

Belzona Facts No altenative considered since the manager of the plant is very happy with both the Belzona materials and the application by the approved contractor. Belzona coating provides long term protection from 98% Sulphuric acid.