

MAIN COOLING WATER PUMPS PROTECTED WITH BELZONA

ID: 985

Industry: Power
Application: CEP-Centrifugal Pumps
Substrate: Cast iron
Products: * Belzona® 1111 (Super Metal) ,
* Belzona® 1341 (Supermetalglide) ,

Customer Location: Coal fired power station - UK
Application Date: 2004

Problem

Erosion corrosion particularly on main wearing rings, cut water and delivery tubes.



Photograph Descriptions

- * Scale of pumps can be gauged from the delivery tubes ,
- * Suction side coated ,
- * Degree of corrosion evident on the delivery tubes ,
- * Completed coating ,

Application Situation

Allen Gwynnes cooling pumps. These pumps are capable of delivering 120,000 gallons of cooling water per minute.

Application Method

Carried out in accordance with Belzona system leaflets CEP-1 and CEP-3. Particular attention was paid to surface preparation with repeated steam cleaning and grit blasting used to remove salt contamination.

Belzona Facts

A competitive ceramic coating had previously been used. Although lower in cost it did not provide the efficiency enhancement that Belzona® 1341 does with its subsequent pay-back. Application still OK in 2007.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

BELZONA
Repair • Protect • Improve