

Belzona LEP System Proven Effective for Wind Turbine Leading Edge Protection

ID: 10304

Industry: Power
Application: FBC-Fans, Blowers and Compressors


Customer Location: Sinan, South Korea
Application Date: September 2024

Substrate: GFRP
Products: Belzona 5711, Belzona 5721

Problem

The client had been using a combination of reinforcement tape and a polyurethane coating system on the wind turbine blade leading edges. However, as blade sizes increased and exposure to rain impact, friction, and erosion intensified, the system was no longer able to provide effective leading-edge protection.

In addition, the system's multi-layer application process was time-consuming, leading to higher operational downtime cost. As a result, the asset owner sought a more durable and efficient leading-edge protection solution.



Damage on wind turbine leading edge



Belzona 5711 rebuilt a wind turbine leading edge



Belzona 5721 was applied as a single-layer coating on a wind turbine leading edge



Closer view of a wind turbine leading edge

Application Situation

The leading-edge protection system was applied in situ using rope access, allowing the work to be completed without removing the blades.

Where required, Belzona 5711 was applied to the leading edges to restore the blade profile and re-establish the substrate geometry. Belzona 5721 was applied as a single-layer coating to provide a durable protective barrier against environmental exposure and operational wear.

Both products were supplied in cartridge format, simplifying the application process, particularly during the summer months, when higher temperatures can reduce the working and cure times of conventional materials.

Application Method

Surface preparation was carried out using sanding to ensure adequate surface roughness and cleanliness of the FRP substrate.

Where require, Belzona 5711 was applied to the leading edges to rebuild the substrate.

Belzona 5721 was applied in a single layer to achieve a thickness of approximately 400–600 microns to protect the wind turbine

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve

Copyright © Belzona International Limited 2026

leading edge.

Belzona Facts

Belzona's LEP system was selected due to its superior performance characteristics, including high adhesion strength, excellent erosion resistance, and the ability to achieve a high-build coating in a single application.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

