Belzona Saves Refinery Millions

ID: 1039

Industry: Oil & Gas Customer Location: Oil Refinery - Tuscaloosa, AL USA

Application: TCC-Tanks and Chemical Containment Application Date: February 2008

Areas

Substrate: Carbon Steel

Products: * Belzona® 1511 (Super HT-Metal),

* Belzona® 1591 (Ceramic XHT),

Problem

Corrosive process fluids and elevated temperatures create an extremely aggressive corrosion rate. If corrosion was not addressed, this vessel would have gone under its minimum wall thickness and forced a shutdown.









Photograph Descriptions

- * Abrasive blasted area ,
- * Repaired area with Belzona® 1511,
- * Application of Belzona® 1591,
- * Finished application after pinhole testing,

Application Situation

Amine regeneration tower operating above 250°F in an environment containing hydrogen sulfide and diglycolamine.

Application Method

Belzona® 1511 and Belzona® 1591 were applied in accordance with Belzona Know-How System Leaflet TCC-5.

Belzona Facts

Possible repairs included a Belzona solution or clad welding the affected area. The Belzona solution required less than \$40,000 of product and labor and was completed in thee days. The clad welding would have required \$100,000 of product and labor and more importantly 10 days. Because daily lost production costs were \$9,000,000, the Belzona solution saved the refinery over \$63,000,000!

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

www.belzona.com

BELZONA