

BELZONA PROTECTS RISER IN SPLASH ZONE

ID: 1242

Industry: Oil & Gas
Application: SOS-Ships and Offshore Structures

Customer Location: Offshore Platform, Adriatic Sea
Application Date: August 2008

Substrate: Wet Carbon Steel
Products: Belzona® 5831 (ST Barrier)

Problem

Corrosion on splash zone



Photograph Descriptions

* Surface preparation by grit-blasting , * Washed application area following blasting , * Applying first coat of Belzona® 5831 , * Applying second coat of Belzona® 5831 ,

Application Situation

Riser splash zone from the rubber boot to approximately 3.0m above the water

Application Method

The application was carried out in accordance with Belzona Know-How System Leaflet SOS-21. Surface preparation by grit-blasting (garnet) followed by two coats of Belzona® 5831 applied to the area.

Belzona Facts

Belzona system was chosen for its ease of application and Belzona® 5831 specifically for its surface tolerance and ability to cure in wet conditions.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

**BELZONA**
Repair • Protect • Improve