FAN BLADES RESTORED WITH BELZONA SYSTEM

ID: 1446

Industry: Power Customer Location: Geothermal power plant, Indonesia

Application: FBC-Fans, Blowers and Compressors Application Date: March, 2009

Substrate: FRP

Products: * Belzona® 1111 (Super Metal),

* Belzona® 1341 (Supermetalglide), * Belzona® 5811 (Immersion Grade),

Problem

Damage and erosion on the leading edges of the blades reduced the overall efficiency and operation of the cooling system.









Photograph Descriptions

- * Damaged cooling tower blades,
- * Repair using Belzona® 1111 in progress,
- * Belzona® 1341 applied to leading edge of blades,
- * Finished repair with Belzona® 5811 applied to blade bodies,

Application Situation

Fan blades from mechanical draft cooling tower

Application Method

The application was carried out in accordance with Belzona Know-How System leaflet FBC-1

Belzona Facts

The client had no other alternative and Belzona saved them time and increased efficency. Belzona® 1341 provides a smooth erosion resistant ling for the leading edge of the fan blades extending maintenance life of the fans.

For more examples of Belzona Know - How In Action, please visit https://khia.belzona.com

ISO 9001:2015 Belzona products are
FS 695214 manufactured under an ISO
ISO 14001:2015 9000 Registered Quality
EMS 695213 Management System.

BELZONA®