

BELZONA DAM LOCK SEALED

ID: 188

Industry: Water / Wastewater
Application: GSS-Gaskets, Seals and Shims
Substrate: Carbon Steel
Products: * Belzona® 2211 (MP Hi-Build Elastomer) ,
* Belzona® 2911 (QD Conditioner) ,

Customer Location: Dam in Florida, U.S.A.
Application Date: November 1998

Problem

Lower seal on locks were leaking due to irregular metal-on-metal seal caused by cavitation.



Photograph Descriptions

- * The culprit ,
- * Surface preparation complete ,
- * Work in progress ,
- * The lock is sealed ,

Application Situation

Locks on Dam

Application Method

Application was carried out in accordance with a modified version of Belzona Know-How leaflets GSS-5 and SOS-10a.

Belzona Facts

Tremendous coordination was necessary between the contractor and the Army Corp of Engineers. Each door of the lock is 47 feet wide. Following surface preparation by grit blasting, product was applied to one side, TurtleWax® used as release agent to entire length of door seal.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com


BELZONA
Repair • Protect • Improve