

BELZONA® SUPERWRAP PIPE REPAIR

ID: 1982

Industry: Oil & Gas
Application: VPF-Valves, Pipes and Fittings
Substrate: Carbon Steel
Products: * Belzona® SuperWrap ,

Customer Location: Major oil producer, North Sea, Norway
Application Date: April 2009

Problem

There were two 10mm holes through wall defects in the pipe caused by local bacterial corrosion. Prior to the application, the defects were sealed with a patch of Belzona® 1211 to provide a temporary leak sealing repair. The client needed the pipe system back in service as soon as possible.



Photograph Descriptions

- * Defective pipe prior to repair ,
- * Grit blasting and preparing the application area ,
- * Second spiral applied ,
- * Finished application ,

Application Situation

A six-inch diameter pipe, carrying produced water, operating at 30-55°C and 1.5-2 Bar pressure.

Application Method

The application was carried out in accordance with the Belzona® SuperWrap Application Working Procedure.

Belzona Facts

A Belzona® SuperWrap repair, compliant to ISO/TS 24817 and ASME PCC-2 Article 4.1, was applied to provide reinforced protection to the weak and vulnerable areas of the corroded pipework. Using a Belzona® SuperWrap repair, the client was able to eliminate the need for hot work and this approach also minimized the time the pipe system was out of service. The pipe repair was completed within two hours and was back to full strength following a forty-eight-hour cure period.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015
FS 695214
ISO 14001:2015
EMS 695213

Belzona products are
manufactured under an ISO
9000 Registered Quality
Management System.

www.belzona.com

